

Revision Date: 03/04/2016

SAFETY DATA SHEET

1. Identification

Material name: SUPER DIAMOND CLEAR

Material: 359A 55

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person:EH&S DepartmentTelephone:216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Skin Corrosion/Irritation Category 2
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B

Unknown toxicity - Health

Acute toxicity, oral 1.47 %
Acute toxicity, dermal 5.1 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 100 %

Environmental Hazards

Acute hazards to the aquatic Category 2

environment

Unknown toxicity - Environment

Acute hazards to the aquatic 64.55 %

environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Revision Date: 03/04/2016



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.

Causes skin irritation. May cause genetic defects.

May cause cancer. Toxic to aquatic life.

Precautionary Statement: Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Wear protective

gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective

equipment as required. Avoid release to the environment.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower. If skin irritation occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Take off contaminated clothing. In case of fire: Use ... to

extinguish.

Storage: Store in well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic petroleum distillates	64742-95-6	30 - 60%
1,2,4-Trimethylbenzene	95-63-6	15 - 40%
1,3,5-Trimethylbenzene	108-67-8	3 - 7%
Xylene	1330-20-7	1 - 5%



Revision Date: 03/04/2016

Cumene	98-82-8	1 - 5%
Ethylbenzene	100-41-4	0.1 - 1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Take off immediately all contaminated clothing. Immediately flush with

plenty of water for at least 15 minutes while removing contaminated

clothing and shoes. Wash contaminated clothing before reuse. Get medical

attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may

cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.



Revision Date: 03/04/2016

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits


Chemical Identity	type	Exposure Limit Va	alues	Source
1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Xylene	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm n	655 ng/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)





Revision Date: 03/04/2016

		100		Luc Mooli B. L. C. C.
	REL	100 ppm	435	US. NIOSH: Pocket Guide to
			mg/m3	Chemical Hazards (2010)
	STEL	150 ppm	655	US. NIOSH: Pocket Guide to
			mg/m3	Chemical Hazards (2010)
	REL	100 ppm	435	US. NIOSH: Pocket Guide to
			mg/m3	Chemical Hazards (2010)
	STEL	150 ppm	655	US. NIOSH: Pocket Guide to
			mg/m3	Chemical Hazards (2010)
	REL	100 ppm	435	US. NIOSH: Pocket Guide to
	112		mg/m3	Chemical Hazards (2010)
	PEL	100 ppm	435	US. OSHA Table Z-1 Limits for Air
	' - -		mg/m3	Contaminants (29 CFR 1910.1000)
			ŭ	(02 2006)
	STEL	150 ppm	655	US. OSHA Table Z-1-A (29 CFR
	SILL		mg/m3	1910.1000) (1989)
	TWA	100 ppm	435	US. OSHA Table Z-1-A (29 CFR
	1 ***	FE	mg/m3	1910.1000) (1989)
	TWA	100 ppm	435	US. Tennessee. OELs. Occupational
	IVVA		mg/m3	Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655	US. Tennessee. OELs. Occupational
	SIEL	.00 pp	mg/m3	Exposure Limits, Table Z1A (06 2008)
	OT FOL		350 µg/m3	US. Texas. Effects Screening Levels
	ST ESL		осо руппо	(Texas Commission on
				Environmental Quality) (07 2011)
	07.50		80 ppb	US. Texas. Effects Screening Levels
	ST ESL		оо ррь	(Texas Commission on
				Environmental Quality) (07 2011)
	411 = 01		42 ppb	US. Texas. Effects Screening Levels
	AN ESL		42 ppb	(Texas Commission on
				Environmental Quality) (07 2011)
	411 = 01		180 μg/m3	US. Texas. Effects Screening Levels
	AN ESL		του μίχιπο	(Texas Commission on
		150 nnm	GEE	Environmental Quality) (07 2011)
	STEL	150 ppm	655	US. California Code of Regulations,
			mg/m3	Title 8, Section 5155. Airborne
		200 nnr		Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations,
				Title 8, Section 5155. Airborne
		100 nnm	105	Contaminants (08 2010)
	TWA	100 ppm	435	US. California Code of Regulations,
	PEL		mg/m3	Title 8, Section 5155. Airborne
Cumono	T\\\\\	E0 mm=		Contaminants (08 2010) US. ACGIH Threshold Limit Values
Cumene	TWA	50 ppm		
		FO	045	(2011)
	PEL	50 ppm	245	US. OSHA Table Z-1 Limits for Air
			mg/m3	Contaminants (29 CFR 1910.1000)
Etter the con-	T) A / A			(02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values
		100		(2011)
	PEL	100 ppm	435	US. OSHA Table Z-1 Limits for Air
			mg/m3	Contaminants (29 CFR 1910.1000)
				(02 2006)





Revision Date: 03/04/2016

Chemical name	type	Exposure Limit	t Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm	651	Canada. Quebec OELs. (Ministry of



Revision Date: 03/04/2016

			mg/m3	Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWAEV	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)



Revision Date: 03/04/2016

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering

Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Use explosion-proof ventilation equipment. Good general ventilation

(typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy

access to water supply and eye wash facilities.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke. Wash

contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Colorless

Odor: Mild petroleum/solvent
Odor threshold: No data available.
pH: No data available.



Revision Date: 03/04/2016

Melting point/freezing point:

Initial boiling point and boiling range:

No data available.

No data available.

Flash Point: 42 °C 108 °F(Setaflash Closed Cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas):

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

1 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

No data available.

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 0.9

Solubility(ies)

Solubility in water:
Solubility (other):
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Decomposition temperature:
No data available.

Viscosity: < 20.5 mm2/s (40 °C 104 °F)

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes skin irritation.



Revision Date: 03/04/2016

Eye contact: Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 12,962.23 mg/kg

Dermal

Product: ATEmix: 11,523.38 mg/kg

Inhalation

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Rat, 4 h): 10,200 mg/m3

1,3,5-Trimethylbenzene LC 50 (Rat, 4 h): 10,200 mg/m3

Xylene LC 50 (Rat, 4 h): 6,350 mg/l

Cumene LC 50 (Mouse, 7 h): 10 mg/l

Ethylbenzene LC 50 (Rat): 55 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Xylene in vivo (Rabbit): Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product: No data available.



Revision Date: 03/04/2016

Specified substance(s):

Aromatic petroleum

in vivo (Rabbit, 24 - 72 hrs): Not irritating

distillates

1,2,4-Trimethylbenzene in vivo (Rabbit, 30 min): Not irritating

1,3,5-Trimethylbenzene in vivo (Rabbit, 30 min): Not irritating

Xylene in vivo (Rabbit, 24 hrs): Moderately irritating

Cumene in vivo (Rabbit, 24 hrs): Not irritating

Ethylbenzene in vivo (Rabbit, 7 d): Slightly irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Cumene Overall evaluation: Possibly carcinogenic to humans.

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Cumene Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.



Revision Date: 03/04/2016

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l

Mortality

1,3,5-Trimethylbenzene LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 42 mg/l Mortality

> LC 50 (Bryconamericus iheringii, 96 h): 9.94 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h): 8.05 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study LC 50 (Bryconamericus iheringii, 96 h): 6.9 mg/l Read-across from

supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h); 7.6 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

Cumene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l

Mortality

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 9.1 - 15.6 mg/l Ethylbenzene

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality

1,3,5-Trimethylbenzene EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication

LC 50 (Water flea (Daphnia magna), 24 h): 150 mg/l Mortality **Xylene**

> EC 50 (Daphnia magna, 48 h): 3.82 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study

EC 50 (Ceriodaphnia dubia, 48 h): > 3.4 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 4.7 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 3.6 mg/l Read-across from supporting

12/17



Revision Date: 03/04/2016

substance (structural analogue or surrogate), Supporting study

Cumene LC 50 (Water flea (Daphnia magna), 24 h): 95 mg/l Mortality

Ethylbenzene LC 50 (Water flea (Daphnia magna), 24 h): 190 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aromatic petroleum

distillates

NOAEL (Daphnia magna, 21 d): 2.6 mg/l read across

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l Experimental result, Key

study

Cumene NOAEL (Danio rerio and Pimephales promelas, 28 d): 0.38 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene NOAEL (Ceriodaphnia dubia, 7 d): 1.17 mg/l Read-across from supporting

substance (structural analogue or surrogate), Key study

NOAEL (Daphnia magna, 21 d): 1.57 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

LOAEL (Daphnia magna, 21 d): 3.16 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

EC 10 (Daphnia magna, 21 d): 1.91 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study

EC 50 (Daphnia magna, 21 d): 2.9 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):



Revision Date: 03/04/2016

Xylene Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 5.5 - < 12.2 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.2 - < 24.2 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.4 - < 18.5 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.7 - < 21.2 Aquatic

sediment Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20

Cumene Log Kow: 3.66

Ethylbenzene Log Kow: 3.15

Mobility in Soil: No data available.

Other Adverse Effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1866, RESIN SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.



Revision Date: 03/04/2016

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity		
Xylene	100 lbs.		
Cumene	5000 lbs.		
Ethylbenzene	1000 lbs.		

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity		
Xylene	100 lbs.		
Cumene	5000 lbs.		
Diisodecyl nhthalate			

Diisodecyl phthalate

Ethylbenzene 1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Aromatic petroleum	500 lbs
distillates	
1,2,4-Trimethylbenzene	500 lbs
1,3,5-Trimethylbenzene	500 lbs
Xylene	500 lbs
Cumene	500 lbs
Ethylbenzene	500 lbs

SARA 313 (TRI Reporting)

Chemical Identity

1,2,4-Trimethylbenzene

Xylene Cumene Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u> <u>Reportable quantity</u>

Xylene 100 lbs.



Revision Date: 03/04/2016

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

1,2,4-Trimethylbenzene 1,3,5-Trimethylbenzene Xylene Cumene

Diethylbenzene, Mixed Isomers

Ethylbenzene

US. Massachusetts RTK - Substance List

Chemical Identity

1,2,4-Trimethylbenzene 1,3,5-Trimethylbenzene Xylene Cumene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

1,2,4-Trimethylbenzene 1,3,5-Trimethylbenzene Xylene Cumene Diisodecyl phthalate

US. Rhode Island RTK

Chemical Identity

1,2,4-Trimethylbenzene Xylene Cumene Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water 648 g/l and exempt solvent):

VOC Method 310: 71.96 %

Inventory Status:

Australia AICS: All components in this product are listed on or

exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.



Revision Date: 03/04/2016

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances: All components in this product are listed on or

exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are listed on or

exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: All components in this product are listed on or

exempt from the Inventory.

US TSCA Inventory: All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals: All components in this product are listed on or

exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this product are

not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 03/04/2016

Version #: 2.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.